

PRODUCT DATA SHEET

5100HD Gas Analyzer for Measuring Moisture in Natural Gas

Based on Tunable Diode Laser Absorption Spectroscopy (TDLAS)

In natural gas operations – pipelines and transmission, gas processing, custody transfer points – moisture (water vapor) analysis is important for multiple reasons. The presence of water can negatively impact the energy value of the gas stream, contribute to hydrate formation and even lead to corrosion of pipes and other hardware.

The AMETEK 5100HD is an extractive-type analyzer designed for hot/wet sample analysis.

The tunable diode laser technique used in the 5100HD is inherently free from many of the problems that can occur with physical-contact sensors – notably degradation of the sensor with repeated exposure to contaminants, and a delayed measurement response to sudden process upsets. The reliability of TDLAS-based analyzers has been proven, as they have been used in refineries, petrochemical plants and in natural gas production operations globally for over a decade. Components analyzed in a variety of background gases include acetylene, carbon monoxide, carbon dioxide, hydrogen sulfide, oxygen and methane.

For natural gas analysis, there is no sample conditioning required for the 5100HD analyzer system, other than particulate filtering and assuring the sample does not condense at the maximum integrated oven temperature of 150°C (302°F). The analyzer uses a completely digital implementation of the Wavelength Modulation Spectroscopy (WMS) approach.

A key feature of the 5100HD is the use of sealed reference cells, which is used to line-lock the laser on a desired wavelength. Any minor shift in the observed spectrum is used as feedback to adjust the laser, ensuring the proper operating wavelength. Thus, there is a real-time confirmation that the laser is locked on the desired absorption line.



KEY BENEFITS

- Non-contact measurement offers low maintenance
- Laser line-lock verification using internal reference cell
- Resistant to contamination
- Modbus, Ethernet and analog connectivity
- Type 4X enclosure houses the electronic components – designed for outdoor installation, in temperature ranging from -20 to 50°C (-4 to 122°F)
- Fully-integrated sample handling



APPLICATIONS

- Custody transfer
- Gas processing
- Dehydration
- Feed stock



KEY MARKETS

- Oil and gas
- Petrochemical
- Refining

PERFORMANCE SPECIFICATIONS

Typical ranges and performance	Ranges: 0-2500 ppm (typical)
Accuracy	±4ppmv or ±2% of reading, whichever is greater
Ambient temperature	-20 to 50°C (-4 to 122°F)
Relative humidity	0 to 90%, non-condensing
Sample flow rate	1-2 LPM (2.1-4.2 SCFH) – application dependent
Sample cell pressure	70 to 170 kPa absolute (10 to 25 psia)
Speed of response	<2 second photometric response. Total system response is dependent on sample flow rate
Electrical requirements	120/240 VAC (108-132V/216-264V), 47-63Hz or 24VDC (22-26VDC)
Power requirements	25-45W without heater, 425-445W with heater – typical
Outputs	Local display Fast ethernet (IEEE802.3) RS485 serial port, isolated (supports Modicon Modbus RTU) (1) single isolated 4-20 mA loop-powered analog output (4) dry relay contacts. Contact rating 30 VAC, 60 VDC, 100 VA resistive
Physical dimensions (W x H x D)	880mm x 674mm x 302mm (34.6 x 26.5 x 11.9in) – typical for NEC/CEC Class I Division 2 and ATEX/IECEx Zone 2 configurations
Weight	60 kgs (132lbs) – typical for NEC/CEC Class I Division 2 and ATEX/IECEx Zone 2 configurations
Enclosure	IP65 and Type 4X
Approvals and certifications	Certified to meet multiple ATEX, IECEx, CSA, NEC and Inmetro standards for hazardous areas. Consult AMETEK for more details

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28 8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2020, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0432 Rev 11 (0524)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments.
Specifications subject to change without notice.

