

PRODUCT DATA SHEET

5100P TDLAS Moisture Analyzer

Lightweight and rugged transportable moisture (water vapor) analyzer delivering reliable, accurate measurements in natural gas

The 5100P analyzer provides simple, easy-to-use moisture analysis using tunable diode laser absorption spectroscopy (TDLAS) in a durable, lightweight, and transportable package for measurements in natural gas. Designed to be intuitive to start-up and log data, the 5100P is the tool-of-choice for users needing to perform measurements in remote locations or verify fixed analyzer installations.

Minimal maintenance required

The non-contact TDLAS sensing technology means that both the laser source and the detector are kept separate from the process. This eliminates the need for routine calibration, cleaning of the sensor or interferences from process contaminants, increasing measurement uptime and reducing total cost of ownership.

To reduce the possibility of over pressuring the cell, or introducing contaminants, an integrated sample conditioning panel is included with the 5100P analyzer.

Measurement confidence

To ensure accurate measurement, every 5100P is factory calibrated and tested prior to shipment. The 5100P also uses an internal reference to line-lock the laser on a desired wavelength. Any minor shift in the observed spectrum is used as feedback to adjust the laser, ensuring the proper operating wavelength. Thus, there is a real-time confirmation that the laser is locked on the desired absorption line.

Increased efficiency

With an integrated sample system, using the 5100P is simple and easy. A measurement can be made in minutes, just connect the sample tubing, power up the analyzer, and start flow through the system. The TDLAS technology in the 5100P delivers immediate response to changes in the moisture content of the natural gas. Users no longer have to wait hours for the sensor to equilibrate and can make more measurements in less time. The 5100P is certified for use in hazardous areas so there are no costly enclosures or hot work permits needed to operate the analyzer.



KEY BENEFITS

- Fast response, highly accurate measurements using TDLAS technology
- Certified for use in hazardous areas
- Integrated sample system removes contaminants
- Rechargeable battery for at least eight hours of operation
- Lightweight package simplifies transporting the device between locations



APPLICATIONS

- Monitoring H₂O in natural gas pipelines, processing and fuel lines



KEY MARKETS

NATURAL GAS

- Transmission pipelines
- Custody transfer
- Dehydration
- Underground storage
- Gas processing
- Gas compressor and metering stations

PERFORMANCE SPECIFICATIONS

Technology	Tunable diode laser absorption spectroscopy
Speed of response	<1 second photometer response; <15 seconds to T90 at 2 SLPM of sample gas
Range	0 – 2500 ppmv
Accuracy	2% of reading or +/- 4 ppmv (whichever is greater)
Repeatability	2% of reading or +/- 4 ppmv (whichever is greater)
Limit of detection	5 ppmv in methane
User interface	On board display and USB
Battery type	Rechargeable sealed lead acid battery
Sample cell pressure	Atmospheric
Ambient temperature	-20 to +50°C (-4 to +122°F)
Sample temperature	-20 to +50°C (-4 to +122°F)
Inlet pressure range for sample panel	1.03 to 17.2 barg (15 to 250 psig)
Recommended sample flow rate	1 to 2 SLPM (2 to 4 SCFH)
Physical dimensions	25.1 cm x 20.9 cm x 40.1 cm (9.9 in x 8.2 in x 15.8 in); approximately 13.2 kg (29.1 lbs)
Sample wetted parts	304 Stainless steel, 316 stainless steel, SiO2 glass, EPDM
Power requirements	110-240 VAC 50-60 Hz for battery charging and instrument use when battery is depleted
Environmental rating	Pollution degree: 2 Overvoltage category: I Maximum altitude: 2000 meters Ingress rating: IP 65
Certifications	ATEX/IEC Ex II 3 G Ex nA ic op pr IIC T3 Gc -20°C ≤ Ta ≤ +50°C CSA/UL Class I Division 2, Groups A-D, T3 -20°C ≤ Tamb ≤ +50°C

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28-8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2020, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0544 Rev 5 (0524)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

