

## PRODUCT DATA SHEET

### 5100P TDLAS

#### Moisture in Carbon Dioxide Analyzer

Lightweight and rugged transportable moisture (water vapor) analyzer delivering reliable, accurate measurements in carbon dioxide streams

Carbon dioxide (CO<sub>2</sub>) pipelines, like natural gas pipelines, require monitoring for leaks caused by corrosion. Combined with CO<sub>2</sub>, any moisture present can lead to corrosion. The 5100P analyzer provides easy-to-use moisture analysis using tunable diode laser absorption spectroscopy (TDLAS) in a durable, transportable package for measurements in CO<sub>2</sub>. Intuitive to start-up and log data, the 5100P is the tool of choice for users needing to perform measurements in remote locations or verify fixed analyzer installations.

#### Minimal maintenance required

The non-contact TDLAS sensing technology means that both the laser source and the detector are kept separate from the process. This eliminates the need for routine calibration, cleaning of the sensor or interferences from process contaminants, increasing measurement uptime and reducing total cost of ownership. To reduce the possibility of over-pressuring the cell, or introducing contaminants, an integrated sample conditioning panel is included.

#### Measurement confidence

To ensure accurate measurement, every 5100P is factory-calibrated and tested prior to shipment. An internal reference prevents wavelength shift when operated in the field. Although the 5100P, with its high-sensitivity, moisture-specific measurement, will not be impacted by other constituents in the CO<sub>2</sub> stream, the laser-source output must be monitored and controlled continuously to deliver an accurate moisture measurement every time.

#### Increased efficiency

With an integrated sample system, using the 5100P is simple and easy. A measurement can be made in minutes, while the TDLAS technology in the 5100P delivers an immediate response to changes in moisture content. Users no longer have to wait hours for the sensor to equilibrate and can make more measurements in less time. The 5100P is certified for use in hazardous areas, so there are no costly enclosures or hot work permits needed to operate the analyzer.



### KEY BENEFITS

- Fast-response, highly accurate measurements using TDLAS technology
- Accurate moisture measurements within minutes of powering up the analyzer
- Lightweight package simplifies transport of the device between locations
- Certified for use in hazardous areas
- Integrated sample system removes contaminants
- Rechargeable battery for at least eight hours of operation



### APPLICATIONS

- Monitor water concentrations in CO<sub>2</sub> removal processes
- Measure water concentrations in CO<sub>2</sub> pipelines
- Identify presence of water in enhanced oil recovery processes, when CO<sub>2</sub> is used
- Ensure CO<sub>2</sub> purity specifications



### KEY MARKETS

- Natural gas processing
- CO<sub>2</sub> transportation and sequestration
- Oil exploration and recovery

## PERFORMANCE SPECIFICATIONS

<b>Technology</b>	Tunable diode laser absorption spectroscopy	
<b>Speed of response</b>	<1 second photometer response; <15 seconds to T90 at 2 SLPM of sample gas	
<b>Range</b>	0 to 100 ppmv	0 to 3500 ppmv
<b>Accuracy</b>	±4 ppmv	2% of reading or ±20 ppmv (whichever is greater)
<b>Repeatability</b>	±4 ppmv	2% of reading or ±20 ppmv (whichever is greater)
<b>Limit of detection</b>	4 ppmv in CO <sub>2</sub>	20 ppmv in CO <sub>2</sub>
<b>User interface</b>	On-board display and USB	
<b>Battery type</b>	Rechargeable sealed lead acid battery	
<b>Sample cell pressure</b>	Atmospheric	
<b>Ambient temperature</b>	-20 to +50°C (-4 to +122°F)	
<b>Sample temperature</b>	-20 to +50°C (-4 to +122°F)	
<b>Inlet pressure range for sample panel</b>	1.03 to 17.2 barg (15 to 250 psig)	
<b>Recommended sample flow rate</b>	1 to 2 SLPM (2 to 4 SCFH)	
<b>Dimensions (W x H x D)</b>	401 x 251 x 209 mm (9.9 x 8.2 x 15.8 in.) approximately 13.2 kg (29.1 lbs)	
<b>Sample wetted parts</b>	304 stainless steel, 316 stainless steel, SiO <sub>2</sub> glass, EPDM	
<b>Power requirements</b>	110-240 VAC 50-60 Hz for battery charging and instrument use when battery is depleted	
<b>Environmental rating</b>	Pollution degree: 2 Overvoltage category: I Maximum altitude: 2000 meters Ingress rating: IP 65	
<b>Certifications</b>	ATEX/IECEx Zone 2 CSA/UL Class I, Div 2, Groups A, B, C, D	

### SALES, SERVICE & MANUFACTURING

#### USA - Pennsylvania

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

#### USA - Delaware

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

#### Canada - Alberta

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

### WORLDWIDE SALES AND SERVICE LOCATIONS

#### USA

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

#### Brazil

Tel: +55 19 2107 4100

#### Germany

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

#### India

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

#### Singapore

Tel: +65 6484 2388  
Fax: +65 6481 6588

#### China

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28 8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2020, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. PI0011 Rev 2 (0524)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments.  
Specifications subject to change without notice.

