

PRODUCT DATA SHEET

IPS-4 NDIR Analyzer

Infrared-based analyzer with integrated sampling conditioning

Finding the right on-line process analyzer for your application can be a time-consuming experience. Users are looking for cost-effective, low-maintenance solutions for gas and liquid analysis.

AMETEK has been offering solutions to meet your specific application needs for well over four decades. The IPS-4 NDIR analyzer, built on our field proven IPS-4 UV-VIS platform, offers unparalleled reliability, and enhanced analog and digital connectivity.

With an integrated sample conditioning system, the IPS-4 analyzer is easy-to-use and is durable enough to be installed in outdoor, wash-down, hazardous, and environmentally harsh locations. While the IPS-4 can be mounted in demanding environments, it still possesses user interfaces expected in production environments.

An interactive display and interface is included with every IPS-4 for local access. Remote access is also available, through both serial and Ethernet connections.



KEY BENEFITS

- Multiple gas capability
 - Carbon monoxide (CO), carbon dioxide (CO₂), methane (CH₄), water (H₂O) and more
- Analog and digital connectivity
 - Modbus, ethernet and web browser-based interface
- NEMA 4 enclosure houses all components
 - Designed for outdoor installation; no exposed components
- Fully integrated sample conditioning
 - No need for site integration



APPLICATIONS

- Water in Acetic Acid
- Water in dehydration systems
- CO₂ in hydrocarbons



KEY MARKETS

- Natural gas
- Refining
- Petrochemical

PERFORMANCE SPECIFICATIONS

Analyzer range	ppm to 100% depending upon specific application
Linearity (independent)	<1% full-scale range
Measurement accuracy	<+/-2% full-scale range (application-specific)
Repeatability	<1% full-scale range (application-specific)
Stability	0.5% of full-scale range
Zero drift	<1.0% of full-scale range over 24 hours
Response time	<2 seconds photometric response, <30 seconds to T90
Components	Up to five components can be measured
Inputs	Two non-isolated analog inputs (0-5V, 0/4-20mA) 2 optically isolated discrete DC inputs 22 key piezoelectric keypad
Outputs	265 x 64 pixel vacuum fluorescent display with multi-lingual capability (language options include English, Spanish, French, German, Russian. This is a partial listing. Contact AMETEK for more information) Two isolated analog outputs (0/4-20 mA) (Two additional analog outputs optional) Eight dry relay contacts (NO, 100VA, 240 V) RS485 isolated (supports MODBUS RTU) RS232 non-isolated Fast Ethernet (IEEE802.3)
Sample system limits	Sample pressure: Up to 100 barg (1450 psig) for some configurations Temperature: Heater capable of maintaining 150°C (300°F)
Utility requirements	Electrical: 120 or 240 VAC (105-132 or 209-264 VAC), 47 to 63 Hz Power consumption: <700 W with sample heater <300 W without sample heater
Instrument air/nitrogen	4.8-6.9 barg (70-100 psig) (valve actuation)
Environmental requirements	Ambient temperature: -20° to 50°C (-4° to 122°F) Ingress protection: IP65 and NEMA 4X Enclosure Material: 316 Stainless Steel
Physical dimensions	Typical model: (W x H x D): 78 cm x 53 cm x 30 cm (30.7" x 20.9" x 11.8") Weight: 66 kg (145 lb) for base system
Approvals and certifications	Meets various ATEX, CEC & NEC, IEC-EX, Korean and Russian hazardous area requirements. Consult AMETEK for specific details.

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39`

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28-8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2024, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0116 Rev 10 (0624)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

