

# PRODUCT DATA SHEET

## WDG-VC

### Flue gas oxygen and combustibles analyzer

The WDG-VC has a close-coupled extractive design that allows for fast response in a wide range of flue gas applications up to 1648°C (3000°F).

#### Reliability

The WDG-VC is designed with measurement redundancy and continual diagnostics functions that validate the health of the analyzer and validate the proper combustion measurements.

#### Safety

SIL-2 approved, capable for use in SIS combustion safety systems. Onboard diagnostics provide low probability of undetected analyzer faults. Communication through Modbus RTU or Fast Ethernet allows remote communication for diagnostics, calibration, verification, and error notification for the safety system.

#### Maintenance

This completely field-serviceable analyzer also has an Ethernet connection that allows remote performance monitoring for maintenance LANs or Asset Management Systems (AMS).



### KEY BENEFITS

- Internal flow sensor for probe tip to exhaust port sample system confidence
- Accurate combustibles (CO<sub>e</sub>) monitoring
- Versatility in flange mounting options, digital communications and data management
- Completely field-serviceable

### APPLICATIONS

- Process heaters
- Steam boilers
- Thermal oxidizers

### KEY MARKETS

- Refining and petrochemical
- Power and steam generation
- Furnace and kilns

## PERFORMANCE SPECIFICATIONS (Moisture applications)

<b>Principle of operation</b>	Zirconium oxide for net oxygen (O <sub>2</sub> ) measurement and dual hot-wire catalytic detectors for COe
<b>Output range</b>	O <sub>2</sub> : From 0-1% to 0-100% COe: 0-500 parts per million (ppm) to 0-10,000 ppm, 0-2% to 0-5% Hydrocarbon: 0-5%
<b>Accuracy</b>	O <sub>2</sub> : ±0.75% of measured value or ±0.05%, whichever is greater COe: ±2% of full-scale output range
<b>Response</b>	O <sub>2</sub> : 90% of a step change < 11 seconds with Flame Arrestors COe: 90% of a step change < 20 seconds with Flame Arrestors
<b>Aspirator air requirements</b>	3 SCFH typical at 3 to 6 psig, instrument air or nitrogen (N <sub>2</sub> )
<b>Analog output</b>	Three isolated linear current outputs for O <sub>2</sub> , combustibles. Each output can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA and is fully scalable. NAMUR configurable. Hold or track during calibration. Max. load 1200 Ω
<b>Alarms</b>	Five independent NO alarms Set relays to energize or de-energize on alarm
<b>Contact rating</b>	0.5A, 30V, 10VA max. non-inductive load, AC or DC
<b>Digital communication</b>	2 wire MODBUS RTU, 57.6 Kbaud
<b>Configuration</b>	MODBUS RTU, AMETEK configuration software, or AMEvision HMI
<b>Diagnostics</b>	Low sample flow, cell and detector age tracking, cell resistance, calibration required, analog current verification
<b>Sample pressure</b>	±6 in. water gauge
<b>Max. sample dewpoint</b>	200°C (392°F)
<b>Max. flue gas temperature/ probe type/lengths</b>	704°C (1300°F)/316 SS/910 to 2740 mm (36 to 108 in.) 1024°C (1875°F)/310 SS/910 to 2740 mm (36 to 108 in.) 1648°C (3000°F)/Hexoloy®/600 to 1820 mm (24 to 72 in.)
<b>Environment</b>	Ambient temperature: -30 to 65°C (-22 to 149°F) Relative humidity: 5 to 95%, non-condensing
<b>Enclosure</b>	Hinged IP65 (NEMA 4X), weather-resistant, stainless steel, purged, and floor mount versions available. UL Class I, Div 2, Gp B, C, D or ATEX II 3G Ex pz IIC T3 Gc and IECEx Zone 2, T3 with purge
<b>Power requirements</b>	115 VAC, ±10%, 47-63 Hz, 740 VA max.; 230 VAC, ±10%, 47-63 Hz, 740 VA max

## SALES, SERVICE &amp; MANUFACTURING

## USA - Pennsylvania

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

## USA - Delaware

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

## Canada - Alberta

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

## WORLDWIDE SALES AND SERVICE LOCATIONS

## USA

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

## Brazil

Tel: +55 19 2107 4100

## Germany

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

## India

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

## Singapore

Tel: +65 6484 2388  
Fax: +65 6481 6588

## China

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28 8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the F-0462 Rev 6 (0224)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

